

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

Important! Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

2112 Tunica with tucks and button closure

Recommendations on fabric:
natural/mixed fabric suitable for
dresses.

You will also need: fusible interfacing,
11 buttons.

CUTTING:

The word, "beam" used on some
patterns means "straight of grain".
Some pieces will be cut on the fold, this
is noted on the pattern piece. Mark all
notches and other design features such
as darts, pleats etc. from the pattern
onto your fabric.



Main fabric:

1. Back - cut 1 on fold
2. Front - cut 2
3. Sleeve - cut 2
4. Sleeve decorative tab - cut 2
5. Stand collar - cut 2

Fusible interfacing:

1. Stand 1

INSTRUCTIONS:

1. Apply fusible interfacing to outer stand collar and to one-piece plackets on the front.
2. Make tucks on front and topstitch them from shoulder seam up to notch (bulk should be on the right side and directed away from center).
3. Serge the edge of one-piece placket on the front. Fold placket onto wrong side, press and topstitch along the marked line.
4. Sew shoulder and side seams, press seams towards back and serge.
5. Pin stand collars together right sides together sew outer edges. Start and stop sewing exactly at the marked line of seam. Clip into curves. Turn the finished stand collar right side out and press.
6. Sew outer stand collar into neckline, press seam allowances at stand collar. Turn under the raw edge of inner stand collar and stitch in the ditch.
7. Fold decorative tabs in half lengthwise right sides together and sew along longer and one shorter edge. Turn right side out, slashing seam allowances in corners, straighten and press. Serge raw shorter edge. Topstitch decorative tabs according to the markings onto the wrong side of sleeves.
8. Sew sleeve seams, press towards back and serge. Sew sleeves into armholes, serge and press.
9. Turn under the hem, and hem of sleeve, two times by 1 cm and topstitch.
10. Make buttonholes on right placket and on stand collar, sew on buttons on the left one. Make buttonholes on decorative tabs. Sew on buttons on sleeves.

Congratulations, your tunica is ready! :)