

If the pattern has a double line around it, the seam allowances are included.

**Note:** By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

**Important!** Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

## 2221 Fleece sweatshirt with zipper

Recommendations on fabric: fleece, footer, or natural/mixed thick knit fabric of small stretchiness. For decoration – knit fabric of high stretchiness in a matching color.

You will also need: a zipper.



### CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Seam allowances: all seams 1 cm.

### Main fabric:

1. Front – cut 1 on fold
2. Back – cut 1 on fold
3. Front yoke – cut 2
4. Sleeve – cut 2

### Fabric 1:

1. Hem facing - cut 1 on fold
2. Cuff – cut 2
3. Stand collar – cut 2

## INSTRUCTIONS:

Advice: sew knit pieces with special elastic/zig-zag stitches. If you use an overlock, cut seam allowances to 0.6-0.8 cm width. Topstitch hem allowances with double needle to save elasticity.

1. Pin front yoke to front along the princess seams and sew up to the beginning of the lower edge of yoke. Clip into the corner of seam allowance on front and serge.
2. Sew shoulder seams. Serge seams and press towards back.
3. Sew the outer stand collar into neckline, slightly stretching it stand collar. Press at stand collar. Sew in zipper. Serge the lower edge of inner stand collar. Pin the inner stand collar, right side down, onto the outer stand collar and sew upper edge. Fold away stand collar onto wrong side and press. Stitch in the ditch the lower edge of the inner collar into the seam. Slipstitch the center edge of inner stand collar to the zipper tape. Sew a decorative stitch along the zipper teeth at 0.5 cm.
4. Close the zipper. Sew the lower edge of the front yoke to the front. Serge and press towards the bottom. Sew a decorative stitch around all edge's yokes at 0.5 cm from seam.
5. Sew sleeves into armholes, matching notches, serge, and press. Sew sleeve seams and continue sewing side seams, serge, and press.
6. Sew cuff into a ring. Press seam apart. Fold cuff in half lengthwise and press. Sew cuff to sleeve, slightly stretching the cuff. Serge.
7. Sew lower facing into a ring. Press seam apart. Fold facing in half lengthwise and press. Sew the facing to the hem, slightly stretching the facing. Serge.

Congratulations, your sweatshirt is ready! :)