

If the pattern has a double line around it, the seam allowances are included.

**Note:** By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

**Important!** Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

## 2266 Colour block jersey jumper

Recommendations on fabric: natural/mixed knit fabric of medium stretchiness in contrasting or similar color.

*Fabric 1* approx. 0.65 m (sizes 32-48), approx. 0.75 m (sizes 50-54) with a fabric width of 150 cm.

*Fabric 2* approx. 0.65 m (sizes 32-48), approx. 0.75 m (sizes 50-54) with a fabric width of 150 cm.



### CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Seam allowances: all seams 1 cm. Seam allowance for hem of sleeve – 1.5 cm.

#### Main fabric 1:

1. Side back – cut 2
2. Side front – cut 2
3. Center front – cut 1 on fold
4. Lower sleeve – cut 2
5. Belt – cut 1 on fold

#### Main fabric 2:

1. Center back – cut 1 on fold

2. Middle front – cut 2
3. Upper sleeve – cut 2

#### INSTRUCTIONS:

Advice: sew knit pieces with special elastic/zig-zag stitches. If you use an overlock, cut seam allowances to 0.6-0.8 cm width. Topstitch hem allowances with double needle to save elasticity.

1. Sew side backs to center back, press towards center and serge.
2. Sew center front to middle front, press towards center and serge. Sew side front to middle front, press towards center and serge.
3. Sew right shoulder seam, press seams towards back and serge.
4. Cut or use ready-made bias tape, its width should equal 4 cm and length should equal the length of neckline + 5 cm. Fold bias tape half lengthwise right side out and press. Pin bias tape to neckline from the right side and sew. Clip into seam allowances. Fold bias tape onto wrong side and topstitch onto main piece along the seam. Press seam.
5. Sew the left shoulder seam, press seams towards back and serge.
6. Sew upper sleeve to lower sleeve, press towards top and serge.
7. Sew sleeves into armholes, serge, and press.
8. Sew side seams processing the sleeve seam at the same time, serge, and press.
9. Sew waistband into a ring, press seam apart. Fold belt in half lengthwise right side out and press. Sew belt to lower edge of garment, slightly stretching it, serge, and press.
10. Serge the lower edge of sleeve, press onto wrong side and topstitch.

Congratulations, your jumper is ready! :)