

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

Important! Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

2483 Longsleeve with voluminous collar

Recommendations on fabric: natural/mixed knit fabric of medium stretchiness.

CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.



Seam allowances: seam allowance for hem of garment and hem of sleeve – 2 cm, other seams - 1.0 cm.

Main fabric:

1. Back – cut 1 on fold
2. Front – cut 1 on fold
3. Sleeve – cut 2
4. Collar – cut 2

INSTRUCTIONS:

1. Sew shoulder seams. Serge seams and press towards back.
2. Pin collars together right sides together and sew outer edge. Turn the collars onto right side and press. Pin right lower collar onto left lower collar and baste together along lower

edges. Sew collar into neckline, clipping into seam allowance near corner. Serge and press towards Shell.

3. Sew side seams, press seams towards back and serge.
4. Sew sleeve seam, serge, and press. Sew sleeves into armholes, serge, and press.
5. Serge hem of garment and lower edge of sleeve, press onto wrong side and topstitch.

Congratulations, your long sleeve is ready! :)