

If the pattern has a double line around it, the seam allowances are included.

**Note:** By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

**Important!** Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

## 2520 High-collar sweatshirt

Recommendations on fabric: fleece, footer, or thick natural/mixed knit fabric of small stretchiness. For decoration – knit fabric of high stretchiness in a matching color.

You will also need: closure-zipper.

CUTTING:



The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Seam allowances: all seams 1 cm.

### Main fabric:

1. Back – cut 1 on fold
2. Center front – cut 1 on fold
3. Side front – cut 2
4. Front yoke – cut 2
5. Sleeve – cut 2
6. Stand collar – cut 2
7. Off-set welt – cut 2
8. Large pocket bag – cut 1
9. Small pocket bag – cut 1

Main fabric 1:

1. Hem facing - cut 1 on fold
2. Cuff – cut 2

INSTRUCTIONS:

Advice: sew knit pieces with special elastic/zig-zag stitches. If you use an overlock, cut seam allowances to 0.6-0.8 cm width. Topstitch hem allowances with double needle to save elasticity.

1. Sew front yoke to front along the vertical edges up to the horizontal line. Clip into the corner of seam allowance on front and serge.
2. Press the welt in half lengthwise wrong sides together. Pin off-set welt onto the right side of center front and sew. Start and stop stitching exactly at the horizontal lines of the off-set welt. Trim away corners, fold the offset welt onto the right side, straighten, press. Sew the shorter ends of the off-set welt to the horizontal seam allowances of the front.
3. Serge the side edges of the smaller pocket bag. Sew the smaller pocket bag into the seam of the off-set welts, press seam. Pin the bigger pocket bag onto the smaller pocket bag and sew the upper edge. Press seam, serge. Slipstitch the bigger pocket bag to center front along the princess seam edge and the lower edge.
4. Sew side fronts to the front, press towards the side seam and serge.
5. Sew shoulder seams, press seams towards back and serge.
6. Sew the outer stand collar into neckline, slightly stretching it stand collar, press seam allowances at stand collar. Sew in zipper. Serge the lower edge of inner stand collar. Pin the inner stand collar, right side down, onto the outer stand collar and sew upper edge. Fold away stand collar onto wrong side and press. Stitch in the ditch the lower edge of the inner collar into the seam. Slipstitch the center edge of inner stand collar to the zipper tape. Sew a decorative stitch along the zipper teeth at 0.5 cm.
7. Close the zipper. Sew the lower edge of the front yoke to front, serge and press towards bottom.
8. Sew sleeves to garment, matching notches, serge, and press. Sew sleeve seams and continue sewing side seams, serge, and press.
9. Sew cuff into a ring, press seam apart. Fold cuff in half lengthwise right side out and

press. Sew cuff to sleeve, slightly stretching the cuff, serge.

10. Sew lower facing into a ring, press seam apart. Fold facing in half lengthwise wrong sides together and press. Sew the facing to the hem, slightly stretching the facing, serge.

Congratulations, your sweatshirt is ready! :)