

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

Important! Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

5788 Chemise / nightdress in romantic style

Recommendations on fabric: : elastic lace with scallops, microfibre.

You will also need: elastic band 0.5 cm wide, ready straps.

CUTTING:

The word, "beam" used on some patterns means "straight of grain". Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Main fabric:

- 1.Back part – 1 detail.
- 2.Side front part – 2 details
- 3.Lower front part – 1 detail

Lace:

- 1.Upper right front part – 1 detail
- 2.Upper left front part – 1 detail

Advice: use special elastic seam or zigzag seam to stitch the parts together. When



overstitching, cut the seam allowances to 0.6 – 0.8 cm. The seam allowance on the edge of the garment is stitched with double seam to ensure stretchiness.

INSTRUCTIONS:

- 1.Sew lower front part to upper front part, serge the seam allowances cutting them to 0.5 cm.
- 2.Sew cup off upper right front part to side front part, serge the seam allowances cutting them to 0.5 cm.
- 3.Sew dart on cup, at the same time sewing relieve seam, serge the seam allowances cutting the dart depth to 0.5 cm.
- 4.Serge lower edge of upper left front part. Put upper right front part onto upper left front part and topstitch along scallops.
- 5.Sew cup of upper left front part to side front part, serge the seam allowances cutting them to 0.5 cm.
- 6.Sew dart on cup, at the same time sewing relieve seam up to marker, serge the seam allowances cutting them to 0.5 cm.
- 7.Serge edges of slit with rolled seam, cutting away seam allowance.
- 8.Sew side seams, serge the seam allowances cutting them to 0.5 cm
- 9.Serge armholes and upper edge of back part with rolled seam. To prevent the details from stretching topstitch elastic band from the wrong side with zigzag stitch stretching the band a bit. The elastic band should be 10% cm shorter than the detail.

Congratulations, your nightdress is ready! :)