

If the pattern has a double line around it, the seam allowances are included.

**Note:** By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

**Important!** Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

## 7087 Sleeveless dress with a fluffy skirt

Recommendations on fabric: lightweight natural fabric

You will also need: invisible zipper; bias tape

### CUTTING:

The word, "beam" used on some patterns means "straight of grain". Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.



### Main fabric:

1. Center back bodice – cut 2
2. Side back bodice – cut 2
3. Upper back panel – cut 2
4. Lower back skirt – cut 2
5. Upper front panel – cut 1
6. Lower front skirt –cut 1
7. Center front bodice – cut 1
8. Side front bodice – cut 2

### INSTRUCTIONS:

1. Sew side front bodice to center front bodice. Clip into curved seams; serge or finish seam. Press toward center.
2. Sew the back side bodice to back bodice. Clip into curved seams; serge or finish seam. Press toward center.
3. Baste the top edge of the back upper panels to the top edge of the two lower back skirt sections. Baste the top edge of the front upper panel to the top edge of the low front skirt.
4. Sew the back skirt sections to the bodice backs. Sew the front skirt to the bodice front. Serge or finish seams and press toward bodice.
5. Sew the garment side and shoulder seams. Serge or finish seams and press towards back. Press the bias tape in half lengthways; Sew the raw edges of the bias tape to the neck edge, turn under and press. Topstitch the folded edge to the garment. Repeat this for the armholes.
6. Serge or finish the back center edges separately. Sew backs together from the zipper mark down to bottom edge of garment. Press the seam apart as well as the opening for the zipper. Sew in the zipper.
7. Serge or finish bottom edges skirts, fold to the wrong side, press and topstitch 0.5 cm.

Congratulations, dress for your princess is ready! :)